

The HyroBlue WiFi Water Softener is the next generation in smart water technology. This advanced water softener will give you the ability to monitor your water from anywhere in the world while protecting your largest investment, your home.



Features

- DROP App allows you to control system from anywhere
- · Water usage data and history
- Provides text messages, emails and/or push notifications for low salt and other system information to your smartphone
- Ability to shut off water to home with Drop App
- Proprietary two valve manual bypass with 1" MNPT connections.
- 5 Year Warranty
- Eliminates hardness (Calcium & Magnesium)
- Demand initiated regeneration
- Treated water refill with pre-brine option
- · Adjustable cycle times
- 9V battery back up for loss of power











The HyroBlue WiFi Water Softener utilizes a patented piston design that provides the ability to shut off water to the home. When paired with DROP Leak Detectors through the DROP Hub, this system provides all the benefits of a top of the line water softener, home leak protection, and a water conservation system in one.

The DROP Hub

The Pro Water Softener requires the function of the DROP Hub. The hub is the connection to everything on the DROP Smart Water Management system. It integrates all of your DROP residential water devices together.

DROP Hub Status

Similar to the mobile setup process, DROP can operate in any network environment, with or without WiFi. The color of your DROP Hub light will indicate to you what connection mode it is in. Here is an overview of each of color modes.



DROP Hub Status Light Red Lost WiFi Signal



DROP Hub Status Light Yellow Direct Connections



DROP Hub Status Light GreenConnected to WiFi Only



DROP Hub Status Light Blue
Connected to WiFi and DROP Connect
Services

Product Specifications	HydroBlue WiFi-M	HydroBlue WiFi-L	HydroBlue WiFi-XL
Capacity / Salt Used per Regeneration	32,000 Grains / 15 lbs	48,000 Grains / 24 lbs	64,000 Grains / 30 lbs
Maximum Clear Iron / Magnesium	5 ppm	5 ppm	5 ppm
Exchange Resin	1.0 ft ³	1.5 ft ³	2.0 ft ³
Mineral Tank	9 x 48 polyglass	10 x 54 polyglass	12 x 52 polyglass
Brine Tank	15x35 polyethylene	15x35 polyethylene	15x35 polyethylene
Service Flow Rate **	10.0 gpm	2.0 gpm	2.4 gpm
Back wash flow rate	78	90	117
Electrical Requirements		12V DC Power Supply (included)	
Battery Backup		9V Battery Backup for power loss	
Product Dimensions and Size	D: 16in W: 27in H: 56in	D: 16in W: 28in H:62in	D: 16in W: 30in H: 60in
Approximate Shipping Weight	100 lbs	133 lbs	164 lbs
** The pressure drop does not exceed 15.0 psi at the service flow rate.			



DROP CONNECT

DROP Hub and Remote

This state-of-the-art smart water monitor is the heart and brains of the DROP Connect smart water monitoring system. It integrates with all your residential water treatment devices. DROP Softeners and Filters require a DROP Hub to function.

The DROP Remote shows the status of your DROP system at a glance and allows you to conveniently turn your water supply on or off. The Remote also extends the range of the DROP Link mesh network.

DROP Leak Detectors

Place DROP Leak Detectors under sinks and dishwashers, behind toilets or washing machines, near your water heater, or anywhere that water might leak or collect. If a leak or freezing temperature is detected, the Leak Detector will have the HyroBlue WiFi Water Softener turn off your water.







